

ICEBERG

06125N

	Modello	Model	Modèle	Modell	Modelo	ICEBERG 06125N 230-1-50	
	Campo applicazione	Application field	Champ e d'application	Anwendungsbereich	Campo d'applicación	+5 ÷ -2	
	Alimentazione	Power supply	Alimentation	Netzanschluß	Alimentación	V/ph/ Hz	230/1+N/50
	Corrente massima assorbita	Maximum absorbed current	Courant absorbé maximum	Maximal absorbierter Strom	Corriente máxima absorbida	A	6,8
	Potenza massima assorbita	Maximum absorbed power	Puissance maximale absorbée	Maximal aufgenommene Leistung	Máxima potencia absorbida	kW	1,2
	Tipo refrigerante	Refrigerant type	Tipe du gaz	Kältemittel	Tipo refrigerante	R404A/R507/ R452A/R448A/ R449A	
	Resa*	Capacity*	Puissance*	Leistung*	Rendimiento*	W	1032
	Pressione sonora a 10 m **	Sound pressure level at 10 m **	Pression acoustique à 10 m **	Schalldruck in 10 m **	Presión sonora a 10 m **	dB(A)	52
	Potenza nominale	Power rating	Puissance nominale	Nennleistung	Potencia nominal	CV	0,5
CMP	Tipo compressore	Compressor type	Type compresseur	Kompressortyp	Tipo compresor	E	
	Passo alette	Fin spacing	Escart alettes	Lamellenabstand	Paso aletas	mm	2,5
CND	Ventilatori	Fans	Ventilateurs	Ventilatoren	Ventiladores	ø mm	1 x ø254
	Potenza nominale assorbita	Nominal power consumption	Puissance nominal absorbée	Nennleistungsaufnahme	Potencia nominal absorbida	W	95
	Portata d'aria	Air volume	Débit d'air	Volumenstrom	Caudal aire	m³/h	700
	Passo alette	Fin spacing	Escart alettes	Lamellenabstand	Paso aletas	mm	6
	Sbrinamento	Defrosting	Dégivrage	Abtauung	Desescarche	EL	
	Espansione	Expansion	Expansion	Expansion	Expansión	VT	
EVP	Ventilatori	Fans	Ventilateurs	Ventilatoren	Ventiladores	ø mm	1 x ø254
	Potenza nominale assorbita	Nominal power consumption	Puissance nominal absorbée	Nennleistungsaufnahme	Potencia nominal absorbida	W	73
	Portata d'aria	Air volume	Débit d'air	Volumenstrom	Caudal aire	m³/h	650
	Freccia d'aria	Air throw	Projection d'air	Reichweite	Flecha de aire	m	6
	Imballo	Packaging	imballo	Imballo	Imballo	X mm	795
A						Y mm	600
						Z mm	865
						X mm	-
B						Y mm	-
						Z mm	-
	Peso lordo	Gross weight	Poids brut	Bruttogewicht	Peso bruto	kg	70
	Peso netto	Net weight	Poids net	Nettogewicht	Peso neto	kg	51
	Volume	Volume	Volume	Volumen	Volúmen	m³	0,41
	Codice	Code	Code	Kodex	Codigo	999908003	

*Resa:Te= -10°C ; Tcond= + 40°C

** Dati derivanti da correlazioni empiriche

C : Capillare / Capillary / Capillaire / Kapillar / Capilar

CMP : Compressore / Compressor / Compresseur / Kompressorleistung / Compresor

CND : Condensatore / Condenser / Condenseur / Verflüssiger / Condensador

EVP : Evaporatore / Evaporateur / Evaporateur / Verdampfer / Evaporador

E : Ermetico / Hermetic / Hermetique / Vollhermetisch / Hermético

G : Gas caldo / Hot gas / Gaz chaud / Heissgas / Gas caliente

P : Potenza frigorifera / Cooling capacity / Puissances frigorifiques / Kälteleistung / Potencia frigorífica

S : Semiermetico / Semihermetic / Semi-hermetique / Halbhermetisch / Semihermético

Ta : Temperatura ambiente / Ambient temperature / Température ambiente / Umgebungstemperatur / Temperatura ambiente

Tc : Temperatura cella / Cold room temperature / Température chambre froid / Kühlraumtemperatur / Temperatura cámara

Te : Temperatura evaporazione / evaporation temperature / température d'évaporation / Verdampfungstemperatur / temperatura de evaporación



Tcond : Temperatura condensazione / condensation temperature / température de condensation / Kondensationstemperatur / temperatura de condensación

Vol : Volume cella / Coldroom volume / Volume chambre / Kühlzellenvolumen / Volúmen cámara

VT : Valvola termostatica / Expansion valve / Détendeur thermostatique / Thermostatisches Expansionsventil Válvula termostática

ICEBERG

Versione Professional
Professional version
Professionnel
Beruflich
Profesional



RESA / VOLUME - CAPACITY / VOLUME - PUISSANCE/ VOLUME - LEISTUNG/ VOLUMEN - RENDIMENTO/ VOLUMEN
Volume calculation conditions: pag. 149

06125 N	Tc	°C	-2				0			
	Ta	°C	27	32	38	43	27	32	38	43
	P	W	1026	957	864	801	1098	1025	939	858
	Vol	m3	6,24	4,94	3,55	2,69	7,85	6,19	4,53	3,33

Disegno tecnico indicativo. Le misure reali potrebbero subire delle variazioni. Indicative technical drawing. Actual measurements may vary.