

ICEBERG

150240SB

	Modello	Model	Modèle	Modell	Modelo		ICEBERG 150240SB-04
	Campo applicazione	Application field	Champ e d'application	Anwendungsbereich	Campo d'applicación		-18 ÷ -22
	Alimentazione	Power supply	Alimentation	Netzanschluß	Alimentación	V/ph/ Hz	400/3+N/50
	Corrente massima assorbita	Maximum absorbed current	Courant absorbé maximum	Maximal absorbierter Strom	Corriente máxima absorbida	A	34,3
	Potenza massima assorbita	Maximum absorbed power	Puissance maximale absorbée	Maximal aufgenommene Leistung	Máxima potencia absorbida	kW	16,8
	Tipo refrigerante	Refrigerant type	Tipe du gaz	Kältemittel	Tipo refrigerante		R404A/R507/ R452A/R448A/ R449A
	Resa*	Capacity*	Puissance*	Leistung*	Rendimiento*	W	12004
	Pressione sonora a 10 m **	Sound pressure level at 10 m **	Pression acoustique à 10 m **	Schalldruck in 10 m **	Presión sonora a 10 m **	dB(A)	53
	Potenza nominale	Power rating	Puissance nominale	Nennleistung	Potencia nominal	CV	15
CMP	Tipo compressore	Compressor type	Type compresseur	Kompressortyp	Tipo compresor		S
	Passo alette	Fin spacing	Escart alettes	Lamellenabstand	Paso aletas	mm	2,5
CND	Ventilatori	Fans	Ventilateurs	Ventilatoren	Ventiladores	ø mm	2 x ø400
	Potenza nominale assorbita	Nominal power consumption	Puissance nominal absorbée	Nennleistungsaufnahme	Potencia nominal absorbida	W	320
	Portata d'aria	Air volume	Débit d'air	Volumenstrom	Caudal aire	m³/h	6000
	Passo alette	Fin spacing	Escart alettes	Lamellenabstand	Paso aletas	mm	8
	Sbrinamento	Defrosting	Dégivrage	Abtauung	Desescarche		EL
	Espansione	Expansion	Expansion	Expansion	Expansión		VT
EVP	Ventilatori	Fans	Ventilateurs	Ventilatoren	Ventiladores	ø mm	2 x ø450
	Potenza nominale assorbita	Nominal power consumption	Puissance nominal absorbée	Nennleistungsaufnahme	Potencia nominal absorbida	W	960
	Portata d'aria	Air volume	Débit d'air	Volumenstrom	Caudal aire	m³/h	11200
	Freccia d'aria	Air throw	Projection d'air	Reichweite	Flecha de aire	m	24
	Imballo	Packaging	imballo	Imballo	Imballo	X mm	2000
A						Y mm	1140
						Z mm	1050
						X mm	2160
B						Y mm	990
						Z mm	990
	Peso lordo	Gross weight	Poids brut	Bruttogewicht	Peso bruto	kg	389
	Peso netto	Net weight	Poids net	Nettogewicht	Peso neto	kg	340
	Volume	Volume	Volume	Volumen	Volúmen	m³	A:2.39 / B:-
	Codice	Code	Code	Kodex	Codigo		999908028

*Resa:Te= -30°C; Tcond= +40°C

** Dati derivanti da correlazioni empiriche

C : Capillare / Capillary / Capillaire / Kapillar / Capilar

CMP : Compressore / Compressor / Compresseur / Kompressorleistung / Compresor

CND : Condensatore / Condenser / Condenseur / Verflüssiger / Condensador

EVP : Evaporatore / Evaporateur / Evaporateur / Verdampfer / Evaporador

E : Ermetico / Hermetic / Hermetique / Vollhermetisch / Hermético

G : Gas caldo / Hot gas / Gaz chaud / Heissgas / Gas caliente

P : Potenza frigorifera / Cooling capacity / Puissances frigorifiques / Kälteleistung / Potencia frigorífica

S : Semiermetico / Semihermetic / Semi-hermetique / Halbhermetisch / Semihermético

Ta : Temperatura ambiente / Ambient temperature / Température ambiente / Umgebungstemperatur / Temperatura ambiente

Tc : Temperatura cella / Cold room temperature / Température chambre froid / Kühlraumtemperatur / Temperatura cámara

Te : Temperatura evaporazione / evaporation temperature / température d'évaporation / Verdampfungstemperatur / temperatura de evaporación




Tcond : Temperatura condensazione / condensation temperature / température de condensation / Kondensationstemperatur / temperatura de condensación

Vol : Volume cella / Coldroom volume / Volume chambre / Kühlzellenvolumen / Volúmen cámara

VT : Valvola termostatica / Expansion valve / Détendeur thermostatique / Thermostatisches Expansionsventil Válvula termostática

ICEBERG

Versione Professional
Professional version
Professionnel
Beruflich
Profesional



RESA / VOLUME - CAPACITY / VOLUME - PUISSANCE/ VOLUME - LEISTUNG/ VOLUMEN - RENDIMENTO/ VOLUMEN
Volume calculation conditions: pag. 149

150240 S B	Tc	°C	-20			
	Ta	°C	27	32	38	43
	P	W	13423	12267	11043	9587
	Vol	m3	402,46	315,34	232,03	164,44

! Max temperatura ambiente: +43°C / Max ambient temperature: +43°C / Température ambiante maximale: + 43°C / Max Umgebungstemperatur: +43°C / Temperatura ambiente maxima: +43°C

Disegno tecnico indicativo. Le misure reali potrebbero subire delle variazioni. Indicative technical drawing. Actual measurements may vary.