

TUAREG S

105445SNI



	Nome	Model	Modell	TUAREG 105445SNI
	Campo di applicazione	Application field	Anwendungsbereich °C	-5 ÷ -15
	Alimentazione	Power supply	Netzanschluß	400/3/50
	Corrente massima assorbita [A]	Max. absorbed current	Max. absorbierter Strom A	55,9
	Potenza massima assorbita [kW]	Max. absorbed power	Max. aufgenommene Leistung kW	13,99
	Tipo refrigerante	Refrigerant type	Kältemittel	R455A
	Classe PED	PED Category	PED-Klasse	III
	PS	PS	PS bar	26
	Pressione sonora a 10 m**	Sound pressure level at 10 m**	Schalldruck in 10 m** dB(A)	51
	Capacità nominale di raffreddamento*	Nominal refrigeration capacity*	Nennkühlleistung W	25364
	COP*	COP*	COP* W/W	2,06
	SEPR	SEPR	SEPR kWh/kWh	2,95
	Consumo annuo di energia elettrica	Annual electrical energy consumption	Jährlicher Stromverbrauch kWh/year	52897
	Tipo compressore	Compressor type	Kompressortyp mm	S+I
CMP	Numero compressori	Compressor number	Anzahl Kompressoren	2
	Controllo di capacità	Capacity control	Kapazitätskontrolle	Inverter
	Minimo fattore di carico	Minimum power factor	Mindestlastfaktor %	22
	Passo alette	Fin spacing	Lamellenabstand mm	2,5
	Volume condensatore	Condenser volume	Kondensatorvolumen l	11,35
	Ventilatori	Fan	Ventilator	4 x Ø450
CND	Tipo ventilatore	Fan type	Ventilatorotyp	EC
	Tipo controllo	Control type	Kontrolltyp	0-10 Vdc
	Pot nominale assorbita	Nom. power cons.	Nennleistungsaufnahme W	2000
	Portata aria	Air volume	Volumenstrom m3/h	10000
	Volume ricevitore	Receiver volume	Empfängerlautstärke l	14,5
	Imballo X	Packing X	Verpackung X mm	2350
	Imballo Y	Packing Y	Verpackung Y mm	1400
	Imballo Z	Packing Z	Verpackung Z mm	1650
	Peso lordo	Gross weight	Bruttogewicht kg	-
	Peso netto	Net Weight	Nettogewicht kg	-
	Volume imballo	Volume	Volumen m3	5,43
	Codice	Code	Kodex	-

N= * :Te= -10°C ; Ta= + 32°C

B= * : Te= -35°C ; Ta= +32°C

** Risultato derivante da correlazioni teoriche



R455A is a flammable refrigerant. Refer to EN 378-1 for charge limits

- CMP : Compressore / Compressor / Compresseur / Kompressorleistung / Compresor
- CND : Condensatore / Condenser / Condenseur / Verflüssiger / Condensador
- E : Ermetico / Hermetic / Hermetique / Vollhermetisch / Hermético
- EC : Ventilatore elettronico / Electronic fan / Ventilateur électronique / Elektronischer Ventilator / Ventilador electrónico
- Pf : Potenza frigorifera / Cooling capacity / Puissances frigorifiques / Kälteleistung / Potencia frigorífica
- Pe : Potenza elettrica assorbita / Electrical power consumption / Consommation électrique / Elektrischer Stromverbrauch / Consumo de energía eléctrica
- S : Semihermetico / Semihermetic / Semi-hermetique / Halbhermetisch / Semihermético
- Ta : Temperatura ambiente / Ambient temperature / Température ambiente / Umgebungstemperatur / Temperatura ambiente
- Te : Temperatura evaporazione / evaporation temperature / température d'évaporation / Verdampfungstemperatur / temperatura de evaporación

dimensionale 4 x 450

TUAREG 105445SNI	Te	°C	-15				-10				-5			
	Ta	°C	27	32	38	43	27	32	38	43	27	32	38	43
	Pf	W	24010	21982	19549	17522	27484	25364	22820	20700	30886	28673	26018	23806
	Pe	W	10664	10927	11244	11508	11931	12290	12721	13080	13272	13727	14272	14727
	COP [W/W]	W/W	2,25	2,01	1,74	1,52	2,30	2,06	1,79	1,58	2,33	2,09	1,82	1,62

! Max temperatura ambiente: +43°C / Max ambient temperature: +43°C / Température ambiante maximale: + 43°C / Max Umgebungstemperatur: +43°C / Temperatura ambiente maxima: +43°C